

S336

Bright SVGA Projector



Features

- Luminous SVGA projection with 4,000 lumens and 25,000:1 contrast ratio
- HDMI, VGA and composite connectivity
- Up to 15,000-hour lamp life
- Vertical keystone for easy positioning
- Integrated 10-watt speaker



Robust I/O and superior performance

Project large SVGA images with the 4,000 lumens Optoma S336. Its 25,000:1 contrast ratio, 1.94 – 2.16:1 throw ratio and 1.1x zoom make it ideal for small-to-medium spaces, such as classrooms, offices and training spaces.

Vertical keystone support simplifies placement for easy installation. An integrated 10-watt speaker delivers crisp, room-filling audio that enhances presentations and videos without additional equipment.

Robust input options, including HDMI, VGA and composite enable connectivity to a wide range of devices. A 15,000-hour lamp life enables many years of use with minimal maintenance.



S336



TECHNICAL SPECIFICATIONS

Aspect Ratio	4:3
Audio	10W speaker
Brightness	4,000 ANSI lumens
Compatible Aspect Ratio	4:3 (native), 16:9 and auto compatible
Connections	1x HDMI v1.4a, 1x VGA, 1x composite, 1x audio-in, 1x USB-A (5v / 1.0 amp), 1x audio-out
Contrast Ratio	25,000:1
Display Technology	Texas Instruments 0.55" SVGA DMD
Displayable Colors	1.07 billion
Keystone Correction	± 40° Vertical
Light Source Type	203W
Light Source Life	15,000/12,000/10,000/6,000 (Eco+/Dynamic/Eco/Bright)
Lens Shift	None
Maximum Resolution	UXGA (1600 x 1200)
Native Resolution	SVGA (800 x 600)
Noise Level	27dB
Offset	115%±5%
Operating Temperature	41-104°F (5-40°C)
Power Consumption	200W Normal (Bright), 160W Standard (ECO), ≥58W Dynamic Mode, 203W (max)
Power Supply	AC input 100-240V, 50-60 Hz, auto-switching
Projection Distance	3.9' - 46.9' (without zoom)
Projection Lens	F = 21.85mm - 24mm
Projection Screen Size	27.7" - 304.4"
Remote Control	IR remote control
Throw Ratio	1.94 - 2.16 ±5%
Uniformity	75%

Zoom Type	1.1x Manual
-----------	-------------

COMPATIBILITY SPECIFICATIONS

3D Compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60, Frame-pack: 1080p24, 720p50 / 60, Over-Under: 1080p24, 720p50 / 60
Computer Compatibility	UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Mac compatible
Horizontal Scan Rate	15.375 - 91.146 KHz
RoHS	Compliant
Vertical Scan Rate	50-85 Hz (120Hz for 3D feature projector)
Video Compatibility	SDTV, HDTV

PHYSICAL SPECIFICATIONS

Dimensions (W x H x D)	12.4" x 3.9" x 9.6"
Security	Security bar, Kensington lock, password protection, keypad lock
Weight	6.7 lbs.

Other

What's in the Box?	S336, AC power cable, remote control, batteries, quick start user manual
--------------------	--

Accessories Part Numbers	Carrying case: BK-4028, Lamp (replacement): BL-FP195D, Remote (replacement): BR-3079N, Universal ceiling mount: BM-5001U
--------------------------	--

UPC	796435 44 499 0
-----	-----------------

Warranty Info	1 Year limited parts and labor warranty on the projector, 90 days lamp warranty
---------------	---

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2021 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.

Published on 01/07/21