

Key Features

Higher Brightness. Longer Lamp Life.

- 22,000:1 contrast ratio
- SuperColor™ technology
- 5 colour modes
- Auto power off
- Vertical keystone



Product Description

The ViewSonic PA503X offers impressive visual performance in small business meeting rooms and classrooms. With higher brightness and longer lamp life, PA503X projector is guaranteed to reproduce the finest of details in any environment for much longer. ViewSonic exclusive SuperColour™ technology offers a wider range of displayable colour ensuring true-to-life colour accuracy in both bright and dark environments without sacrificing image quality.



Visit Us

www.viewsonic.com

SPECIFICATION

| | |
|---|--|
| Native Resolution: | 1024x768 |
| Brightness: | 3800 (ANSI Lumens) |
| Contrast Ratio with SuperEco Mode: | 22000:1 |
| Display Color: | 1.07 Billion Colors |
| Light Source Type: | Lamp |
| Light Source Life (hours) with Normal Mode: | 5000 |
| Light Source Life (hours) with SuperEco Mode: | 15000 |
| Lamp Watt: | 190W |
| Lens: | F=2.56-2.68, f=22-24.1mm |
| Projection Offset: | 120%+/-5% |
| Throw Ratio: | 1.96-2.15 |
| Optical Zoom: | 1.1x |
| Digital Zoom: | 0.8x-2.0x |
| Image Size: | 30"-300" |
| Throw Distance: | 1.19m-13.11m(100"@3.98m) |
| Keystone: | +/- 40° (V) |
| Audible Noise (Normal): | 31dB |
| Audible Noise (Eco): | 27dB |
| Input Lag: | 16ms |
| Resolution Support: | VGA(640 x 480) to FullHD(1920 x 1080) |
| HDTV Compatibility: | 480i, 480p, 576i, 576p, 720p, 1080i, 1080p |
| Video Compatibility: | NTSC, PAL, SECAM |
| Horizontal Frequency: | 15K-102KHz |
| Vertical Scan Rate: | 23-120Hz |

INPUT

| | |
|-------------------------------------|------------------------|
| Computer in (share with component): | 2 |
| Composite: | 1 |
| HDMI: | 1 (HDMI 1.4/ HDCP 1.4) |
| Audio-in (3.5mm): | 1 |

OUTPUT

| | |
|--------------------|----|
| Monitor out: | 1 |
| Audio-out (3.5mm): | 1 |
| Speaker: | 2W |

CONTROL

| | |
|-----------------------------|---|
| RS232 (DB 9-pin male): | 1 |
| USB Type Mini B (Services): | 1 |

OTHERS

| | |
|--|---|
| Power Supply Voltage: | 100-240V+/- 10%, 50/60Hz (AC in) |
| Power Consumption: | Normal: 260W Standby: <0.5W |
| Operating Temperature: | 0~40°C |
| Carton: | Brown |
| Net Weight: | 2.2kg |
| Gross Weight: | 3.24Kg |
| Dimensions (WxDxH) with Adjustment Foot: | 294x218x110mm |
| Packing Dimensions: | 365x300x188mm |
| OSD Language: | English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages |
| User Guide Language: | English, S-Chinese, T-Chinese, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Total 15 languages |

STANDARD ACCESSORY

| | |
|-----------------|---------------|
| Power Cord: | 1 |
| VGA Cable: | 1 |
| Remote Control: | 1 |
| QSG: | Yes |
| Air Filter: | Yes (CN Only) |
| Warranty Card: | Yes (CN Only) |

OPTIONAL ACCESSORY

| | |
|---------------------|-------------|
| Lamp/Light Source: | RLC-108 |
| Air Filter: | RSPL |
| Wall/Ceiling Mount: | PJ-WMK-007 |
| Carry Bag: | PJ-CASE-008 |