

# X400LVe

## Bright XGA Projector



### Features

- Luminous XGA projection with 4,000 lumens and 25,000:1 contrast ratio
- HDMI, VGA and composite connectivity
- Up to 15,000-hour lamp life
- Vertical keystone for easy positioning
- Integrated 10-watt speaker



### Robust I/O and superior performance

Experience luminous XGA images with the 4,000 lumens Optoma X400LVe. Its 25,000:1 contrast ratio, 1.94 - 2.15:1 throw ratio and 1.1x zoom make it ideal for small-to-medium spaces, such as classrooms, offices and training spaces.

Vertical keystone support simplifies placement for easy installation. An integrated 10-watt speaker delivers crisp, room-filling audio that enhances presentations and videos without additional equipment.

Robust input options, including HDMI, VGA and composite enable connectivity to a wide range of devices. A 15,000-hour lamp life enables many years of use with minimal maintenance.



# X400Lve



## TECHNICAL SPECIFICATIONS

<b>Aspect Ratio</b>	4:3
<b>Audio</b>	10W speaker
<b>Brightness</b>	4,000 ANSI lumens
<b>Compatible Aspect Ratio</b>	4:3 (native), 16:9 and auto compatible
<b>Connections</b>	1 x HDMI v1.4a, 1 x VGA, 1 x composite, 1 x audio-in, 1 x USB-A (5v / 1.0 amp), 1 x VGA, 1 x audio-out, 1 x RS232
<b>Contrast Ratio</b>	25,000:1
<b>Control Unit</b>	RS-232C
<b>Display Technology</b>	Texas Instrument 0.55" XGA DMD
<b>Displayable Colors</b>	1.07 billion
<b>Keystone Correction</b>	± 40° Vertical
<b>Light Source Type</b>	203W
<b>Light Source Life</b>	15,000/12,000/10,000/6,000 (Eco+/Dynamic/Eco/Bright)
<b>Lens Shift</b>	None
<b>Maximum Resolution</b>	UXGA (1600 x 1200)
<b>Native Resolution</b>	XGA (1024 x 768)
<b>Noise Level</b>	27dB
<b>Offset</b>	115% ±5%
<b>On-Screen Display</b>	Complete on-screen menu adjustments in 26 languages
<b>Operating Temperature</b>	Sea Level to 10,000 feet (@73°F); must manually switch to high-altitude mode at 5,000 feet & above
<b>Power Consumption</b>	200W Normal (Bright), 160W Standard (ECO), ≥58W Dynamic Mode, 203W (max)
<b>Power Supply</b>	AC input 100-240V, 50-60Hz, auto-switching
<b>Projection Distance</b>	3.9' - 46.9' (without zoom)
<b>Projection Lens</b>	F=2.41~2.53 ; f = 21.85~24 mm
<b>Projection Method</b>	Front, rear, ceiling count, tabletop
<b>Projection Screen Size</b>	27.7" - 304.4"

<b>Remote Control</b>	IR remote control
<b>Throw Ratio</b>	1.94 - 2.15 ±5%
<b>Uniformity</b>	80%
<b>Zoom Type</b>	1.1x Manual

## COMPATIBILITY SPECIFICATIONS

<b>3D Compatibility</b>	Side-by-Side: 1080i50 / 60, 720p50 / 60, Frame-pack: 1080p24, 720p50 / 60, Over-Under: 1080p24, 720p50 / 60
<b>Computer Compatibility</b>	WUXGA, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA resized, VESA, PC and Mac
<b>Horizontal Scan Rate</b>	15.3 - 91.1kHz
<b>RoHS</b>	Compliant
<b>Vertical Scan Rate</b>	50-85 Hz (120Hz for 3D feature projector)
<b>Video Compatibility</b>	SDTV, HDTV

## PHYSICAL SPECIFICATIONS

<b>Dimensions (W x H x D)</b>	12.4" x 3.9" x 9.6"
<b>Security</b>	Security bar, Kensington lock, password protection, keypad lock
<b>Weight</b>	6.7 lbs.

## Other

<b>What's in the Box?</b>	X400Lve, AC power cable, remote control, batteries, quick start user manual
<b>Accessories Part Numbers</b>	Carrying case: BK-4028, Lamp (replacement): BL-FP195D, Remote (replacement): BR-3079N, Universal ceiling mount: BM-5001U
<b>UPC</b>	796435 44 497 6
<b>Warranty Info</b>	1 Year limited parts and labor warranty on the projector, 90 days lamp warranty

\*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

**Optoma.com**

Copyright © 2021 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.

Published on 01/07/21